Current Transformer

Model 15

APPLICATION:
With ammeters, energy management systems and instrumentation

FREQUENCY:
50-400 Hz..

INSULATION LEVEL:
600 Volts. 10 kV BIL. full wave

WINDOW DIAMETER:
0.94”

APPROXIMATE WEIGHT:
0.9 lbs.

CONNECTIONS:
-Non-standard lead length can be specified
-Flexible leads are UL 1015 105° C CSA approved, #16 AWG, 24" long
-Terminals are brass studs No. 8-32 UNC with one flat washer, lockwasher, and regular nut

CERTIFICATIONS:

E257877

237637

Model	15SFT
Window Size	0.94
Width	2.67
Height	2.75
Depth	1.38

MODEL 15
Window Diameter 0.94”
Approximate weight: 0.9 lbs.

CATALOG NUMBER	CURRENT RATIO	ACCURACY AT 60 HZ	BURDEN VA AT 60 HZ
15SFT-500	50:5	± 1.5%	2
15SFT-600	60:5	± 1.5%	2
15SFT-750	75:5	± 1.5%	2.5
15SFT-800	80:5	± 1.0%	2
15SFT-101	100:5	± 1.0%	2
15SFT-121	120:5	± 1.0%	3
15SFT-1250	125:5	± 1.0%	4
15SFT-151	150:5	± 1.0%	5
15SFT-1750	175:5	± 1.0%	10
15SFT-201	200:5	± 1.0%	12.5





Products are manufactured in a plant whose quality management system is certified / registered as being in conformity with ISO 9001